

<b>Head Office:</b> Refrigeration & Oxygen Co. Ltd. P.O. Box 501 Safat 13006, Kuwait	<b>Email Id:</b> info@rocq8.com  <b>Web Address:</b> www.airtecgulf.com
<b>Dubai Office:</b> Emirates Industrial Gases Co. LLC. P.O. Box 3763, Dubai, UAE	<b>Emergency Phone</b> Kuwait <b>+965 1844 844</b> Dubai <b>+971 8005414</b> Qatar <b>+974 44114603/4/5</b> Bahrain <b>+973 17400469/473</b>
<b>Qatar Office:</b> Qatar Oxygen Co. W.L.L P.O. Box 22386, Doha, Qatar	<b>Facsimile Phone</b> Kuwait <b>+965 2484 3020</b> Dubai <b>+971 42664168</b> Qatar <b>+974 44114350</b> Bahrain <b>+973 17400391</b>
<b>Bahrain Office:</b> Bahrain Medical & Industrial Gas Plant P.O.Box 80738, Kingdom of Bahrain	

## 1. CHEMICAL PRODUCT

PRODUCT NAME: CARBON DIOXIDE IN NITROGEN      SYNONYMS: None

## 2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient Name	Formula	CAS #	Concentration	Exposure Limits (PPM)			
				ACGIH TLV	OSHA PEL	MAC	Other STEL
CARBON DIOXIDE	CO2	124-38-9	BALANCE	5000	5000	5000	30000
NITROGEN	N2	7727-37-9	1-50%	S/A	S/A	S/A	S/A

Note: NE = NONE ESTABLISHED      S/A = SIMPLE ASPHYXIANT

## 3. HAZARD IDENTIFICATION

\* \* \* EMERGENCY OVERVIEW \* \* \*

High pressure gas.  
 Can cause rapid suffocation.  
 Can increase respiration and heart rate.

### POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation

ACUTE EFFECTS: Exposure to carbon dioxide at 1-4% concentrations results in increased respiratory volume. Concentrations greater than 4% produce labored breathing and is dangerous for even a few minutes. Mixture can act as a simple asphyxiant by displacing air necessary for life. Symptoms include rapid respiration, muscular incoordination, fatigue, dizziness, nausea, vomiting, unconsciousness, and death.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: None known

OTHER EFFECTS OF OVEREXPOSURE: None

CARCINOGENICITY (US ONLY):

NTP - No

IARC MONOGRAPHS - No

OSHA REGULATED - No

#### 4. FIRST AID MEASURES

**INHALATION:** Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

**EYE CONTACT:** None

**SKIN CONTACT:** None

**INGESTION:** None

**IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN**

**NOTE TO PHYSICIAN:** None

#### 5. FIRE FIGHTING MEASURES

**FLASH POINT:** Nonflammable

**AUTOIGNITION TEMPERATURE:** N/Av

**FLAMMABLE LIMITS:** Nonflammable

LOWER:

UPPER:

**EXTINGUISHING MEDIA:** Use what is appropriate for surrounding fire.

**SPECIAL FIRE FIGHTING INSTRUCTION AND EQUIPMENT:** Wear self-contained breathing apparatus and full protective clothing. Keep fire exposed cylinders cool with water spray. If possible, stop the product flow.

**HAZARDOUS COMBUSTION PRODUCTS:** None

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Cylinder rupture may occur under fire conditions.

#### 6. ACCIDENTAL RELEASE MEASURES

**CLEAN UP PROCEDURES:** Shut off source if possible and remove source of heat. Remove leaking cylinder to exhaust hood or safe outdoor area if this can be done safely.

**SPECIALIZED EQUIPMENT:** None

### 7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store in well ventilated areas. Keep valve protection cap on cylinders when not in use.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain concentrations below exposure limits and to avoid asphyxiation.

EYE / FACE PROTECTION: Safety glasses

SKIN PROTECTION: None

RESPIRATORY PROTECTION: In case of leakage, use self-contained breathing apparatus.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless

ODOR: Odorless

PHYSICAL PRESSURE: Gas

VAPOR PRESSURE: @20 deg.C: N/Ap

VAPOR DENSITY (AIR=1): 0.970-1.080

BOILING POINT (C): N/Ap

SOLUBILITY IN WATER: cm<sup>3</sup>/100cm<sup>3</sup> H<sub>2</sub>O: 1.485

SPECIFIC GRAVITY (H<sub>2</sub>O=1): Gas

EVAPORATION RATE: Gas

ODOR THRESHOLD: None

### 10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Storage near a heat source.

MATERIALS TO AVOID: Carbon dioxide reacts with alkaline materials. Carbon dioxide decomposes when heated above 1700 degrees celsius. Nitrogen reacts with Li, Nd, and Ti at high temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: None

### 11. TOXICOLOGICAL INFORMATION

LETHAL CONCENTRATION (LC50): None established

LETHAL DOSE 50 (LD50): N/Ap

TERATOGENICITY: N/Ap

REPRODUCTIVE EFFECTS: N/Ap

MUTAGENICITY: N/Ap

### 12. ECOLOGICAL INFORMATION

No adverse ecological effects are expected.

### 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. If the cylinders are the refillable type, return cylinders to supplier with any valve outlet plugs or caps secured and valve protection caps in place.

### 14. TRANSPORT INFORMATION

CONCENTRATION: 1-50%

DOT DESCRIPTION (US ONLY):

PROPER SHIPPING NAME: Compressed gas, n.o.s.  
HAZARD CLASS: 2.2 (nonflammable gas)  
IDENTIFICATION NUMBER: UN1956  
REPORTABLE QUANTITIES: None  
LABELING: NONFLAMMABLE GAS

ADR / RID (EU Only): Class 2, 1A

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well ventilated truck.

## 15. REGULATORY INFORMATION

OSHA: Process Safety Management: Minor component is not listed in appendix A of 29 CFR 1910.119 as a highly hazardous chemical.

TSCA: Mixture is not listed in TSCA inventory.

SARA: The threshold planning quantity for material is 10,000 lbs.

EU NUMBER: N/Ap

NUMBER IN ANNEX 1 OF DIR 67/548: Mixture is not listed in annex 1.

EU CLASSIFICATION: N/Av

R: 20

S: 9,23

## 16. OTHER INFORMATION

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

ABBREVIATIONS: N/Ap - Not Applicable N/Av - Not Available SA - Simple Asphyxiant NE - None Established

**Use proper connections; do not use adapters. Do not force fit!!**

### **DISCLAIMER**

**The information and recommendations in this Material Safety Data Sheet relate only to the specific material mentioned herein and do not relate to use otherwise ie.in combination with any other material or in any process.**

**The information and recommendations herein are taken from our extensive experiences and the data contained in recognized references and believed by us to be true. Refrigeration group of companies make no warranties either expressed or implied with respect there to and assume no liability in connection with the use of such information and recommendation.**