

Head Office:	Refrigeration & Oxygen Co. Ltd. P.O. Box 501 Safat 13006, Kuwait	Email Id:	info@rocq8.com
Dubai Office:	Emirates Industrial Gases Co. LLC. P.O. Box 3763, Dubai, UAE	Web Address:	www.airtecgulf.com
Qatar Office:	Qatar Oxygen Co. W.L.L P.O. Box 22386, Doha, Qatar	Emergency Phone	
Bahrain Office:	Bahrain Medical & Industrial Gas Plant P.O.Box 80738, Kingdom of Bahrain	Kuwait	+965 1844 844
		Dubai	+971 8005414
		Qatar	+974 44114603/4/5
		Bahrain	+973 17400469/473
		Facsimile Phone	
		Kuwait	+965 2484 3020
		Dubai	+971 42664168
		Qatar	+974 44114350
		Bahrain	+973 17400391

1. CHEMICAL PRODUCT

PRODUCT NAME: **CARBON DIOXIDE**

SYNONYMS: **Carbonic Anhydride, Carbonic Acid Gas**

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient Name	Formula	CAS #	Concentration	Exposure Limits (PPM)			
				ACGIH TLV	OSHA PEL	MAC	Other STEL
CARBON DIOXIDE	CO2	124-38-9	99+%	5,000	5,000	5,000	30,000

Note: NE = NONE ESTABLISHED

S/A = SIMPLE ASPHYXIAN

3. HAZARD IDENTIFICATION

***** EMERGENCY OVERVIEW *****
 High pressure liquid and gas.
 Can cause rapid suffocation.
 Can increase respiration and heart rate.
 May cause frostbite.

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: **Inhalation**

ACUTE EFFECTS: Exposure to carbon dioxide at 1-4% concentrations results in increased respiratory volume. Material acts as a simple asphyxiate by displacing air necessary for life. Symptoms include rapid respiration, muscular incoordination, fatigue, nausea and vomiting and unconsciousness. Liquid may cause frostbite. Pressure drop through valves and piping may cause extreme cold and frostbite on contact.

CHRONIC EFFECTS: **None known**

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: **None known**

OTHER EFFECTS OF OVEREXPOSURE: **None**

CARCINOGENICITY (US ONLY):

NTP - No

IARC MONOGRAPHS - No

OSHA REGULATED – No

4. FIRST AID MEASURES

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

EYE CONTACT: None

SKIN CONTACT: If frostbite occurs, flush affected areas with lukewarm water. DO NOT USE HOT WATER.

INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: None

5. FIRE FIGHTING MEASURES

FLASH POINT: Nonflammable

AUTOIGNITION TEMPERATURE: N/Ap

FLAMMABLE LIMITS: Nonflammable

LOWER:

UPPER:

EXTINGUISHING MEDIA: Use what is appropriate for surrounding fire.

SPECIAL FIRE FIGHTING INSTRUCTION AND EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing. Keep fire exposed cylinders cool with water spray.

HAZARDOUS COMBUSTION PRODUCTS: Toxic carbon monoxide may be given off during combustion.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cylinder rupture may occur under fire conditions. Carbon dioxide decomposes when heated above 1700 degrees celsius.

6. ACCIDENTAL RELEASE MEASURES

CLEAN UP PROCEDURES: Shut off source if possible and remove source of heat. Remove leaking cylinder to exhaust hood or safe outdoor area if this can be done safely.

SPECIALIZED EQUIPMENT: None

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store in well ventilated areas. Keep valve protection cap on cylinders when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain concentration below exposure limits.

EYE / FACE PROTECTION: Safety glasses. A face shield is also recommended when handling cold liquid, solid or vapor.

SKIN PROTECTION: Loose fitting gloves of impermeable material, such as leather, when working with cold liquid, solid or vapor.

RESPIRATORY PROTECTION: Use a self-contained breathing apparatus in case of emergency or non-routine use.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless

ODOR: Odorless

PHYSICAL PRESSURE: Gas

VAPOR PRESSURE: @20 deg.C: 816 psig

VAPOR DENSITY (AIR=1): 1.53

BOILING POINT (C): Sublimes -78.4

SOLUBILITY IN WATER: v/v @68 deg.F: 87.8

SPECIFIC GRAVITY (H2O=1): 1.56

EVAPORATION RATE: N/Av

ODOR THRESHOLD: N/Ap

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Storage near a heat source.

MATERIALS TO AVOID: This weakly acidic material will react with alkaline materials to form carbonates and bicarbonates.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: Toxic carbon monoxide when heated above 1700 deg.C.

11. TOXICOLOGICAL INFORMATION

LETHAL CONCENTRATION (LC50): NONE ESTABLISHED

LETHAL DOSE 50 (LD50): N/Ap

TERATOGENICITY: N/Ap

REPRODUCTIVE EFFECTS: N/Ap

MUTAGENICITY: N/Ap

12. ECOLOGICAL INFORMATION

No adverse ecological effects are expected.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. If the cylinders are the refillable type, return cylinders to supplier with any valve outlet plugs or caps secured and valve protection caps in place.

14. TRANSPORT INFORMATION

CONCENTRATION: 99+%

DOT DESCRIPTION (US ONLY):

PROPER SHIPPING NAME: Carbon Dioxide
HAZARD CLASS: 2.2 (nonflammable)
IDENTIFICATION NUMBER: UN1013
REPORTABLE QUANTITIES: None
LABELING: NONFLAMMABLE GAS

ADR / RID (EU Only): Class 2, 2a

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well ventilated truck.

15. REGULATORY INFORMATION

OSHA: Process Safety Management: Material is not listed in appendix A of 29 CFR 1910.119 as highly hazardous chemical.

TSCA: Material is listed in TSCA inventory.

SARA: The threshold planning quantity for material is 10,000 lbs.

EU NUMBER: 204-696-9

NUMBER IN ANNEX 1 OF DIR 67/548: Not listed in annex 1.

EU CLASSIFICATION: None

R: As

S: 9,23

16. OTHER INFORMATION

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

ABBREVIATIONS: N/Ap - Not Applicable N/Av - Not Available SA - Simple Asphyxiant NE - None Established

Use proper connections; do not use adapters. Do not force fit!!

DISCLAIMER

The information and recommendations in this Material Safety Data Sheet relate only to the specific material mentioned herein and do not relate to use otherwise ie.in combination with any other material or in any process.

The information and recommendations herein are taken from our extensive experiences and the data contained in recognized references and believed by us to be true. Refrigeration group of companies make no warranties either expressed or implied with respect there to and assume no liability in connection with the use of such information and recommendation.